

Technical Data Sheet

EOLO Pup Food

- ✓ Ether based food grade TPU wall, with anti-shock rigid PVC spiral
- ✓ Smooth inside, corrugated outside
- ✓ Excellent resistance to abrasion and hydrolysis
- ✓ Resistant to most chemicals
- ✓ Very light weight and flexible



FDA Reg. Cfr.21-Item 17.2600 (aqueous and fatty food) Reg. EU 10/2011, classes A, B, C, D2



Hose & Ducting



Certificate Number: 14362
 ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

Web: www.epdm.co.uk

E-Mail: Sales@epdm.co.uk

Contact

Telephone: +44 (0)1625 573971
 FAX: +44 (0)1625 573250
 Munsch & Co/PTM Ltd
 Units AG2/3 Clarence Mill
 Clarence Road, Bollington
 Macclesfield, Cheshire
 SK10 5JZ
 United Kingdom

Hose & Ducting

Part number	Ø Ins.	Min. wall thick.	Max wall thick.	Weight	Vac.	Bending r.	Coil lgth.	Volume
	mm	mm	m	g/m	mH2O	mm	m	m ³
EP 01 030.0 000.0	30	0,8	3,0	250	3,5	100	30	0,083
EP 01 035.0 000.0	35	0,8	3,3	290	3	120	30	0,101
EP 01 038.0 000.0	38,1	0,8	3,3	310	3	130	30	0,114
EP 01 040.0 000.0	40	1,0	3,6	350	3	140	30	0,133
EP 01 045.0 000.0	45	1,0	4,0	440	3	160	30	0,150
EP 01 052.0 000.0	50,8	1,0	4,5	550	3	175	30	0,201
EP 01 060.0 000.0	60	1,0	4,5	640	3	200	30	0,241
EP 01 063.0 000.0	63,5	1,0	4,5	670	3	230	30	0,293
EP 01 070.0 000.0	70	1,0	4,5	750	3	250	30	0,364
EP 01 076.0 000.0	76,2	1,0	4,5	780	2,5	270	30	0,432
EP 01 080.0 000.0	80	1,0	5,0	900	2,5	290	30	0,485
EP 01 090.0 000.0	90	1,0	5,2	1050	2,5	360	30	0,573
EP 01 100.0 000.0	100	1,0	5,7	1250	2,5	400	30	0,713
EP 01 102.0 000.0	102	1,0	5,7	1270	2,5	400	30	0,725
EP 01 120.0 000.0	120	1,0	5,9	1500	2,5	470	30	0,962
EP 01 127.0 000.0	127	1,0	5,9	1600	2,5	500	30	1,120
EP 01 130.0 000.0	130	1,0	5,9	1650	2,5	520	30	1,145
EP 01 140.0 000.0	140	1,0	6,0	1800	2	570	30	1,646
EP 01 150.0 000.0	151,5	1,0	6,4	2000	2	600	20	1,262
EP 01 203.0 000.0	203,2	1,2	8,9	2900	1	400	20	1,768
EP 01 254.0 000.0	254	1,2	8,9	3600	1	500	10	2,175
EP 01 305.0 000.0	304,8	1,2	8,9	4300	0,8	610	10	2,581

Ideal for delivery of liquid foodstuffs.

Medium suction of dry food such as grains, animal feed, sugar, flour with moderate abrasion power.



-40°C +80°C



Certificate Number: 14362
 ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

Web: www.epdm.co.uk

E-Mail: Sales@epdm.co.uk

Contact

Telephone: +44 (0)1625 573971

FAX: +44 (0)1625 573250

Munsch & Co/PTM Ltd

Units AG2/3 Clarence Mill

Clarence Road, Bollington

Macclesfield, Cheshire

SK10 5JZ

United Kingdom