

Technical Data Sheet

Multipurpose Hose

Product Information



Flexible PVC/NBR hose reinforced with a braided Polyester yarn

For applications that require a flexible and oil-resistant hose

Temperature range -20°C to +80°C

Part number	Ø ins	Ø out	Weight	WP	Bending R.	Coil Lgth.	Vol.
	[mm]	[mm]	[g/m]	[bar]	[mm]	[m]	[m³]
MP 01 006.0 013.0	6	13	146	20	30	100	0.025
MP 01 008.0 015.0	8	15	177	20	40	100	0.030
MP 01 010.0 017.0	10	17	208	20	50	100	0.041
MP 01 013.0 020.0	13	20	254	20	70	100	0.065
MP 01 016.0 023.0	16	23	300	20	80	100	0.100
MP 01 019.0 028.0	19	28	465	20	100	100	0.126
MP 01 025.0 034.0	25	34	584	20	130	100	0.220

Hose & Ducting



Certificate Number: 14352
 ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

Web: www.epdm.co.uk

E-Mail: Sales@epdm.co.uk

Contact

Telephone: +44 (0)1625 573971
 FAX: +44 (0)1625 573250
 Munsch & Co/PTM Ltd
 Units AG2/3 Clarence Mill
 Clarence Road, Bollington
 Macclesfield, Cheshire
 SK10 5JZ
 United Kingdom