

## Technical Data Sheet

### Neoduct 2S



#### Product Information

Wall: Two ply's of Neoprene coated glass -fibre fabric with an embedded bronze plated steel wire helix. Double outer glass cord.

Applications: Exhaust gas, industrial ventilation, automotive, and plastic industries

Temperature range: -55°C + 130°C (peaks 150°C / -67°F +266°F (peaks 302°F)

Part number	Inside Ø mm	WP Bar	Vacuum m H2O	Bending R. Mm	Weight g/m	Length m
P835025	25	2.5	7	25	145	4
P835032	32	2.5	5.8	32	180	4
P835038	38	2.4	5.8	38	210	4
P835041	41	2.4	5.8	41	238	4
P835051	51	2.4	5.3	51	285	4
P835063	63	2.2	4.6	63	355	4
P835070	70	2.2	4.6	70	435	4
P835083	83	2.1	4	83	510	4
P835089	89	2.1	4	89	545	4
P835102	102	1.8	3.5	102	610	4
P835127	127	1.5	2.1	127	860	4
P835152	152	1.1	1.7	152	1100	4
P835160	160	0.9	1.5	160	1146	4
P835178	178	0.8	1.4	178	1275	4
P835203	203	0.6	1	203	1390	4
P835254	254	0.4	0.7	254	1780	4
P835305	305	0.2	0.5	305	2170	4

Hose & Ducting



Certificate Number: 14352  
 ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

Web: [www.epdm.co.uk](http://www.epdm.co.uk)

E-Mail: [Sales@epdm.co.uk](mailto:Sales@epdm.co.uk)

#### Contact

Telephone: +44 (0)1625 573971  
 FAX: +44 (0)1625 573250  
 Munsch & Co/PTM Ltd  
 Units AG2/3 Clarence Mill  
 Clarence Road, Bollington  
 Macclesfield, Cheshire  
 SK10 5JZ  
 United Kingdom