



Technical Data Sheet

Platinum Cured Silicone Rubber

CHEMICAL DESCRIPTION: PHYSICAL PROPERTIES

Polysiloxane, PMQ, VMQ

PHISICAL PROPERTIES	
TENSILE STRENGTH:	1000 .
COMPRESSION SET: 24 Hours @ 150°C	% Max.
ELONGATION AT BREAK:	600% Min.
SPECIFIC GRAVITY:	1.18 G/CC
TEAR:	135 ppi Die "B"
HARDNESS RANGE:	60° Sh. A +/- 5 ° Sh.
TEMPERATURE RANGE:	-60° - +230° C Continuous, +250° C Intermittent
OZONE RESISTANCE:	Excellent
RESILIENCE:	Poor
CHEMICAL RESISTANCE	
WATER:	Good
WATER: ACIDS:	Good Poor

"Premium Grade Peroxide Free" silicone sheeting is designed to be used where higher physical properties are required and in applications that require a low volatile and low outgassing material. Most volatiles and outgassing occur in rubber from the peroxide catalysts that are used to cure the material. This material uses a very clean, high end platinum cure system that is peroxide free. This type of cure system is most common among medical grade materials. We have tailored it to fit in many industrial applications where peroxide can cause problems to the end user. The material is available in continuous rolls or sheets. It is resistant to extreme high and low temperatures, and is proven to be an excellent gasketing material.

- Extremely Low Volatile / Low Outgassing
- Extreme High & Low Temperature Resistance
- UV / Ozone Resistant
- All FDA approved ingredients
- Low Compression Set



Complies with FDA Food Contact Regulation 21 CFR177-2600

Contact

Telephone: +44 (0)1625 573971 FAX: +44 (0)1625 573250 Munsch & Co/PTM Ltd Units AG2/3 Clarence Mill Clarence Road, Bollington Macclesfield, Cheshire SK10 5JZ United Kingdom

ELASTOMERS



ISO 9001

Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.



www.epdm.co.uk

E-Mail: Sales@epdm.co.uk