

Technical Data Sheet

Flame Retardant Neoprene Sponge (WCM180)

SPONGE & FOAM

CHEMICAL DESCRIPTION:	CR
PHYSICAL PROPERTIES	
TENSILE STRENGTH: (ASTM D412)	1.27 KPa
COLOUR:	Grey
DENSITY (ISO 485-88 – ASTM D3575)	170-220 Kg/m ³
HARDNESS:	38-55 Sh 00
COMPRESSION STRENGTH @ 25%	35 - 63 KPa
WATER ABSORPTION:	< 5%
ULTIMATE ELONGATION: (ASTM D412)	>250%
TEAR RESISTANCE: (ASTM D624)	0.58 kn/m
OZONE RESISTANCE:	Very Good
TEMPERATURE RANGE:	-20 - +100°C
FIRE RESISTANCE:	UL94 - HF1 from 2mm to 8mm
SPECIFICATION:	ASTM D1056-00 2C2 B2C
AFNOR NF F 16-101/88:	<i>Grid 5</i>
Fire Reaction	M2
Smoke Reaction	F3
Smoke Index	44

WCM180 is a good quality flame retardant Neoprene sponge which can be used where the risk of flame is evident. Care should be taken regards self-adhesive backings as most are not flame retardant.



Certificate Number: 14352
 ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

www.epdm.co.uk

E-Mail: Sales@epdm.co.uk

Contact

Telephone: +44 (0)1625 573971
 FAX: +44 (0)1625 573250
 Munsch & Co/PTM Ltd
 Units AG2/3 Clarence Mill
 Clarence Road, Bollington
 Macclesfield, Cheshire
 SK10 5JZ
 United Kingdom